



**MODEL 24V I 36V** 

# A VERSATILE WORK TOOL **CONFIGURATIONS.**

The MP-240 is an economic and cost-effective vehicle that can adapt to any industry. It's narrow and maneuverable enough to fit through door openings, but tough enough to withstand years of abuse. It'll move you and your stock three times faster than on foot, quickly boosting operational productivity. Features include under-seat battery compartment, low-step entry, and front and lateral protection bars. Optional lift-out battery box and fold-down back seat. A multi-purpose vehicle offering great value and day-to-day reliability.



### 6 SPEED (Kmh) LOAD CAPACITY TURNING RADIUS MODELS PASSENGERS 1,800 24V 230 900 14 36V 230 2,700 1,800

# **FEATURES**

- Reinforced bolt-on front and rear bumpers
- Time-saving lift-out 2 battery compartment
- Fatigue- and accident-saving 3 ergonomicsuspension
  - Built-to-last all-steel \_\_\_\_ unibody construction
  - Heavy-duty powder 5 paint & protection









# **SPECIFICATIONS**



PERFORMANCE	24V
□ LOAD CAPACITY	230 Kg
☐ TOWING CAPACITY	900 Kg
SPEED	11 Kmh
TURNING RADIUS	1,800 mm
PASSENGERS	1
C DRAWBAR PULL - NORMAL	445 N
C DRAWBAR PULL - ULTIMATE	1,779 N

#### **POWERTRAIN**

#### **OPERATOR COMPARTMENT**

MOTOR	5 HP brushless AC motor	STEERING	Handlebar	
CONTROLLER	SEPEX Electronic speed controller	SEATS	Bucket seat on slide adjusters	
DRIVE AXLE	Helical gear differential	INDICATORS Battery status indicator		
BRAKES	Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake, regenerative braking	SAFETY	Reverse alarm, Deadman foot switch, Horn	
WHEELS	4.8x8 LRC pneumatic tires	ACCESSORIES	Bolt-on bumpers and rear wheel guards, 24V accessories to equalize cells and extend battery life.	
TRANSMISSION Direct drive				
SUSPENSION	Dual coil springs & shock absorbers on front, dual coil springs and shock absorber on rear			

#### ENERGY


#### CHASSIS


VOLTAGE 24V		BODY	14-G diamond-plate steel body, tubular frame, powder coating.	
BATTERY	BATTERY Four 6V-225AH batteries COLOUR		Security orange or federal yellow	
CHARGER	High-frequency (85-265VAC / 45-65Hz, 1kw), built-in and automatic.	LIGHTS	Dual LED headlights & tail/brake lights	


#### **DIMENSIONS**

	DECK		UNIT WEIGHT	г	BATTERY
1,000 mm	HEIGHT	630 mm	WITH BATTERIES	363 Kg	HEIGHT
1,980 mm	LENGTH	500 mm	WITH OUT BATTERIES	218 Kg	LENGTH
760 mm	WIDTH	760 mm			WIDTH
1,270 mm					WEIGHT-MIN
178 mm					WEIGHT-MAX
	1,980 mm 760 mm 1,270 mm	1,000 mm	1,000 mm	1,000 mm       HEIGHT       630 mm       WITH BATTERIES         1,980 mm       LENGTH       500 mm       WITH OUT BATTERIES         760 mm       WIDTH       760 mm         1,270 mm       WIDTH       760 mm	1,000 mm       HEIGHT       630 mm       WITH BATTERIES BATTERIES BATTERIES       363 Kg         1,980 mm       LENGTH       500 mm       WITH OUT BATTERIES       218 Kg         760 mm       WIDTH       760 mm         1,270 mm

Vehicle shown may have optional accessories and is provide for illustrative purposes only 1 Specifications and standard equipment are subject to change without notice.











## **SPECIFICATIONS**



PERFORMANCE	36V		
□ LOAD CAPACITY	230 Kg		
☐ TOWING CAPACITY	2,700 Kg		
SPEED	14.4 Kmh		
TURNING RADIUS	1,800 mm		
PASSENGERS	1		
C DRAWBAR PULL - NORMAL	667 N		
C DRAWBAR PULL - ULTIMATE	2,224 N		

#### **POWERTRAIN**

#### **OPERATOR COMPARTMENT**

MOTOR	10 HP brushless AC motor	STEERING Handlebar		
CONTROLLER	SEPEX Electronic speed controller	SEATS Bucket seat on slide adjusters		
DRIVE AXLE	Helical gear differential	INDICATORS Battery status indicator		
BRAKES	Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake, regenerative braking	SAFETY Reverse alarm, Deadman foot switch, Horn		
WHEELS	4.8x8 LRC pneumatic tires	ACCESSORIES  Bolt-on bumpers and rear wheel guards, 24V acc to equalize cells and extend battery life.		
TRANSMISSION	Direct drive			
SUSPENSION	Dual coil springs & shock absorbers on front, dual coil springs and shock absorber on rear			

#### ENERGY

VOLTAGE	36V	BODY	14-G diamond-plate steel body, tubular frame, powder coating.	
BATTERY	Six 6V-225AH batteries	COLOUR	Security orange or federal yellow	
CHARGER	High-frequency (85-265VAC / 45-65Hz, 1kw), built-in and automatic.	LIGHTS	Dual LED headlights & tail/brake lights	

**CHASSIS** 

#### **DIMENSIONS**

VEHICLES		DECK		UNIT WEIGHT		BATTERY
HEIGHT	1,160 mm	HEIGHT	630 mm	WITH BATTERIES	417 Kg	HEIGHT
LENGTH	2,000 mm	LENGTH	500 mm	WITH OUT BATTERIES	227 Kg	LENGTH
WIDTH	760 mm	WIDTH	760 mm			WIDTH
WHEEL BASE	1,440 mm					WEIGHT-MIN
GROUND CLEARANCE	178 mm					WEIGHT-MAX

Vehicle shown may have optional accessories and is provide for illustrative purposes only 1 Specifications and standard equipment are subject to change without notice.

