



MODEL 24V I 36V

MITATED BUT NEVER EQUALED.

It's no surprise the competition envies our original design. This agile and versatile personnel carrier has it all: A narrow deck, four wheels for greater stability on rough terrain, powerful motor, rugged automotive differential, and larger self-adjusting drum brakes, all-steel unibody construction, bolt-on front bumper and sidebar protection, easy-to-access under-seat battery compartment... The list keeps going. It can also pull up to 2,700 Kg.*, making it a great tow tractor.



\mathcal{C} LOAD CAPACITY TOWING CAPACITY SPEED (Kmh) TURNING RADIUS 24V 230 900 1,900 1 1,900 36V 13 230 2,700

FEATURES

- Safe and comfortable 1 all-steel cabs
- Heavy-duty braking power 2
- Time-saving lift-out battery 3 compartment
 - Built-to-last all-steel 4 unibody construction
 - Heavy-duty powder 5 paint & protection









SPECIFICATIONS



PERFORMANCE	24V
□ LOAD CAPACITY	230 Kg
■ TOWING CAPACITY	900 Kg
SPEED .	11 Kmh
TURNING RADIUS	1,900 mm
PASSENGERS	1
C DRAWBAR PULL - NORMAL	
C DRAWBAR PULL - ULTIMATE	

POWERTRAIN

OPERATOR COMPARTMENT

MOTOR	6 HP brushless AC motor	STEERING	Automotive steering wheel
CONTROLLER	SEPEX Electronic speed controller	SEATS	Bucket seat on slide adjusters
DRIVE AXLE	Helical gear differential	INDICATORS	Battery status indicator
BRAKES	Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake, regenerative braking	SAFETY	Reverse alarm, deadman seat switch, horn
WHEELS	4.8x8 LRC pneumatic tires	ACCESSORIES	Bolt-on bumpers and rear wheel guards, 24V accessories to equalize cells and extend battery life.
TRANSMISSION	Direct drive		
SUSPENSION	Dual coil springs and shock absorber on rear		


ENERGY CHASSIS


VOLTAGE	LTAGE 24V BO		14-G diamond-plate steel body, tubular frame
BATTERY	Four 6V-225AH batteries	COLOUR	Security orange or federal yellow
CHARGER	High-frequency (85-265VAC / 45-65Hz, 1kw), built-in and automatic	LIGHTS	Dual LED headlights & tail/brake lights


DIMENSIONS

	DECK		UNIT WEIGHT	BATTERY
1,140 mm	HEIGHT	630 mm	WITH BATTERIES	HEIGHT
1,930 mm	LENGTH	500 mm	WITH OUT BATTERIES	LENGTH
760 mm	WIDTH	760 mnm		WIDTH
1,320 mm				WEIGHT-MIN
				WEIGHT-MAX
	1,930 mm 760 mm	1,140 mm HEIGHT 1,930 mm LENGTH 760 mm WIDTH	1,140 mm	1,140 mm HEIGHT 630 mm WITH BATTERIES 1,930 mm LENGTH 500 mm WITH OUT BATTERIES 760 mm WIDTH 760 mnm

Vehicle shown may have optional accessories and is provide for illustrative purposes only | | Specifications and standard equipment are subject to change without notice.











SPECIFICATIONS



PERFORMANCE	зеv
□ LOAD CAPACITY	230 Kg
□ TOWING CAPACITY	2,700 Kg
SPEED .	13 Kmh
TURNING RADIUS	1,900 mm
PASSENGERS	1
C DRAWBAR PULL - NORMAL	
C DRAWBAR PULL - ULTIMATE	

POWERTRAIN

OPERATOR COMPARTMENT

MOTOR	10 HP brushless AC motor	STEERING	Automotive steering wheel
CONTROLLER	SEPEX Electronic speed controller	SEATS	Bucket seat on slide adjusters
DRIVE AXLE	Helical gear differential	INDICATORS	Battery status indicator
BRAKES	Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake, regenerative braking	SAFETY	Reverse alarm, deadman seat switch, horn
WHEELS 4.8x8 LRC pneumatic tires		ACCESSORIES	Bolt-on bumpers and rear wheel guards, 24V accessories to equalize cells and extend battery life.
TRANSMISSION Direct drive			
SUSPENSION	Dual coil springs and shock absorber on rear		

ENERGY

VOLTAGE	36V	BODY	14-G diamond-plate steel body, tubular frame
BATTERY	Six 6V-225AH batteries	COLOUR	Security orange or federal yellow
CHARGER	High-frequency (85-265VAC / 45-65Hz, 1kw), built-in and automatic	LIGHTS	Dual LED headlights & tail/brake lights

CHASSIS

DIMENSIONS

VEHICLES		DECK		UNIT WEIGHT	BATTERY
HEIGHT	1,140 mm	HEIGHT	630 mm	WITH BATTERIES	HEIGHT
LENGTH	1,930 mm	LENGTH	500 mm	WITH OUT BATTERIES	LENGTH
WIDTH	760 mm	WIDTH	760 mnm		WIDTH
WHEEL BASE	1,320 mm				WEIGHT-MIN
GROUND CLEARANCE					WEIGHT-MAX

Vehicle shown may have optional accessories and is provide for illustrative purposes only | | Specifications and standard equipment are subject to change without notice.

