



MODEL 6 Passengers I 8 Passengers I 10 Passengers I 11 Passengers I Wheelchair

# THE BEST WAY TO MOVE UP TO 6 PASSENGERS.

This fully customizable vehicle is designed for moving large groupsquickly, safely and comfortably. It can efficiently pull two passengers carts in all sorts of conditions and climb hills with ease. Its wellbalanced design and short turning radius ensure superiormaneuverability with responsive steering and braking. Its lighttouchaccelerator means a smoother ride, while its industrialbatteries and cell equalization converter mean more trips percharge. Available in unlimited configurations, including forwardfacing or back-to-back seating. Optional wheelchair ramp.



MODELS	LOAD CAPACITY (Kg.)	L TOWING CAPACITY (Kg.)		SPEED (Kmh)	TURNING RADIUS (mm)
6 pass.	1,360	2,700	6	16	3,150 mm
8 pass.	1,360	2,700	8	16	3,683 mm
10 pass.	1,360	2,700	10	16	3,683 mm
11 pass.	1,360	2,700	11	16	3,683 mm
Vheelchair	1,360	2,700	6	16	3,683 mm

### **FEATURES**

1	Reinforced bolt-on front and rear bumpers
2	Heavy-duty braking power
3	atigue- and accident-saving ergonomic suspension
4	Built-to-last all-steel unibody construction
5	Heavy-duty powder paint & protection



SITECRAFT 🥩



PERFORMANCE	6 pass.
	1,360 Kg
	2,700 Kg
SPEED	16 Kmh
TURNING RADIUS	3,150 mm
PASSENGERS	6
C DRAWBAR PULL - NORMAL	
DRAWBAR PULL - ULTIMATE	

POWERTRAI	N	OPERATOR	COMPARTMENT		
MOTOR	15 hp shunt motor	STEERING	Automotive steering wheel		
CONTROLLER	Electronic speed controller	SEATS	Two bucket seats on slide adjusters		
DRIVE AXLE	Differential with automotive ring gear	INDICATORS	Battery status indicator		
BRAKES	Rear hydraulic brakes, 11", regenerative braking	SAFETY	Deadman seat switch		
WHEELS	5.7x8 LRC pneumatic tires	ACCESSORIES	Horn		
TRANSMISSION	Goodyear Eagle Synchronous drive				
SUSPENSION	Dual leaf springs on front and rear				


ENERGY		CHASSIS			
VOLTAGE	48V	BODY	14-G diamond-plate steel body, tubular frame		
BATTERY	Eight 6V-220AH batteries	COLOUR	Security orange or federal yellow		
CHARGER	High-Frequency Charger, improves battery performance, prevents current surge, 50/60HZ, 110/220VAC	LIGHTS	LED dual headlights & tail/brake lights		


#### DIMENSIONS

VEHICLES		DECK		UNIT WEIGHT	BATTERY
HEIGHT	1,168 mm	HEIGHT	686 mm	WITH BATTERIES 748 Kg	HEIGHT
LENGTH		LENGTH	1,118 mm	WITH OUT Batteries	LENGTH
WIDTH	1,118 mm	WIDTH	1,930 mm		WIDTH
WHEEL BASE	1,524 mm				WEIGHT-MIN
GROUND Clearance					WEIGHT-MAX

Vehicle shown may have optional accessories and is provide for illustrative purposes only 1 Specifications and standard equipment are subject to change without notice.







SITECRAFT 🥩





PERFORMANCE	8 pass.
	1,360 Kg
	2,700 Kg
SPEED	16 Kmh
TURNING RADIUS	3,683 mm
PASSENGERS	8
C DRAWBAR PULL - NORMAL	
C DRAWBAR PULL - ULTIMATE	

POWERTRAIN		OPERATOR COMPARTMENT		
MOTOR	15 hp shunt motor	STEERING	Automotive steering wheel	
CONTROLLER	Electronic speed controller	SEATS	Two bucket seats on slide adjusters, plus 3bench type	
DRIVE AXLE	Differential with automotive ring gear	INDICATORS	Battery status indicator	
BRAKES	4 wheels 11", regenerative braking	SAFETY	Deadman seat switch, reverse alarm, seat belts	
WHEELS	5.7x8 LRC pneumatic tires	ACCESSORIES	Horn, Bolt-on Front Bumper, DC/DC converter to equalize battery cells	

ENERGY		CHASSIS	
VOLTAGE	48V	BODY	14-G diamond-plate steel body, tubular frame
BATTERY	Eight 6V-244AH batteries	COLOUR	Security orange or federal yellow
CHARGER	High-Frequency Charger, improves battery performance, prevents current surge, 50/60HZ, 110/220VAC	LIGHTS	LED dual headlights & tail/brake lights

#### DIMENSIONS

SUSPENSION


VEHICLES		DECK		UNIT WEIGHT		BATTERY
HEIGHT	1,168 mm	HEIGHT	686 mm	WITH BATTERIES 748	3 Kg	HEIGHT
LENGTH		LENGTH	1,118 mm	WITH OUT BATTERIES		LENGTH
WIDTH	1,118 mm	WIDTH	1,930 mm			WIDTH
WHEEL BASE	1,524 mm					WEIGHT-MIN
GROUND Clearance						WEIGHT-MAX


Vehicle shown may have optional accessories and is provide for illustrative purposes only 1 Specifications and standard equipment are subject to change without notice.



TRANSMISSION Goodyear Eagle Synchronous drive

Dual leaf springs on front and rear





SITECRAFT 🥩





PERFORMANCE	10 pass.
	1,360 Kg
	2,700 Kg
SPEED	16 Kmh
C TURNING RADIUS	3,683 mm
PASSENGERS	10
C DRAWBAR PULL - NORMAL	
C DRAWBAR PULL - ULTIMATE	

POWERTRA	N	<b>OPERATOR</b>	COMPARTMENT		
MOTOR	15 hp shunt motor	STEERING	Automotive steering wheel		
CONTROLLER	Electronic speed controller	SEATS	Two bucket seats on slide adjusters, plus 3bench type		
DRIVE AXLE	Differential with automotive ring gear	INDICATORS	Battery status indicator		
BRAKES	Rear hydraulic brakes, 11", regenerative braking	SAFETY	Deadman seat switch, reverse alarm, seat belts		
WHEELS	5.7x8 LRC pneumatic tires	ACCESSORIES	Horn, Bolt-on Front Bumper		
TRANSMISSIO	Goodyear Eagle Synchronous drive				
SUSPENSION	Dual leaf springs on front and rear				


ENERGY		CHASSIS	
VOLTAGE	48V	BODY	14-G diamond-plate steel body, tubular frame
BATTERY	Eight 6V-220AH batteries	COLOUR	Security orange or federal yellow
CHARGER	High-Frequency Charger, improves battery performance, prevents current surge, 50/60HZ, 110/220VAC	LIGHTS	LED dual headlights & tail/brake lights


#### DIMENSIONS

VEHICLES		DECK	UNIT WEIGHT	BATTERY
HEIGHT		HEIGHT	WITH BATTERIES 748 Kg	HEIGHT
LENGTH	3556 mm	LENGTH	WITH OUT BATTERIES	LENGTH
WIDTH	1,727 mm	WIDTH		WIDTH
WHEEL BASE	1,524 mm			WEIGHT-MIN
GROUND Clearance				WEIGHT-MAX

Vehicle shown may have optional accessories and is provide for illustrative purposes only 1 Specifications and standard equipment are subject to change without notice.







SITECRAFT 🛩





PERFORMANCE	11 pass.
	1,360 Kg
	2,700 Kg
SPEED	16 Kmh
✓ TURNING RADIUS	3,683 mm
PASSENGERS	11
C DRAWBAR PULL - NORMAL	
DRAWBAR PULL - ULTIMATE	


POWERTRAIN		OPERATOR COMPARTMENT	
MOTOR	15 hp shunt motor	STEERING	Automotive steering wheel
CONTROLLER	Electronic speed controller	SEATS	Two bucket seats on slide adjusters,
DRIVE AXLE	Differential with automotive ring gear	INDICATORS	Battery status indicator
BRAKES	Rear hydraulic brakes, 11", regenerative braking	SAFETY	Deadman seat switch
WHEELS	5.7x8 LRC pneumatic tires	ACCESSORIES	Horn, Bolt-on Front Bumper
TRANSMISSION	Goodyear Eagle Synchronous drive		
SUSPENSION	Dual leaf springs on front and rear		


ENERGY		CHASSIS	
VOLTAGE 48V		BODY	14-G diamond-plate steel body, tubular frame
BATTERY	Eight 6V-220AH batteries	COLOUR	Security orange or federal yellow
CHARGER	25 amp, built-in, automatic	LIGHTS	LED dual headlights & tail/brake lights

#### DIMENSIONS

VEHICLES		DECK	UNIT WEIGHT		BATTERY
HEIGHT		HEIGHT	WITH BATTERIES <sup>74</sup>	48 Kg	HEIGHT
LENGTH	3556 mm	LENGTH	WITH OUT BATTERIES		LENGTH
WIDTH	1,727 mm	WIDTH			WIDTH
WHEEL BASE	1,524 mm				WEIGHT-MIN
GROUND Clearance					WEIGHT-MAX

Vehicle shown may have optional accessories and is provide for illustrative purposes only 1 Specifications and standard equipment are subject to change without notice.





SITECRAFT 🥩





PERFORMANCE	Wheelchair	
	1,360 Kg	
	2,700 Kg	
SPEED	16 Kmh	
C TURNING RADIUS	3,683 mm	
PASSENGERS	6	
C DRAWBAR PULL - NORMAL		
C DRAWBAR PULL - ULTIMATE		

POWERTRAIN		OPERATOR COMPARTMENT		
MOTOR	15 hp shunt motor	STEERING	Automotive steering wheel	
CONTROLLER	Electronic speed controller	SEATS	Two bucket seats on slide adjusters,	
DRIVE AXLE	Differential with automotive ring gear	INDICATORS	Battery status indicator	
BRAKES	4 wheels 11", regenerative braking	SAFETY	Deadman seat switch, reverse alarm, seat belts	
WHEELS	5.7x8 LRC pneumatic tires	ACCESSORIES	Horn, Bolt-on Front Bumper, DC/DC converter to equalize battery cells	
TRANSMISSION	Goodyear Eagle Synchronous drive			
SUSPENSION	Dual leaf springs on front and rear			


ENERGY		CHASSIS	
VOLTAGE		BODY	14-G diamond-plate steel body, tubular frame
BATTERY	Eight 6V-244AH batteries	COLOUR	Security orange or federal yellow
CHARGER	High-Frequency Charger, improves battery performance, prevents current surge, 50/60HZ, 110/220VAC	LIGHTS	LED dual headlights & tail/brake lights


#### DIMENSIONS

VEHICLES	DECK	UNIT WEIGHT	BATTERY
HEIGHT	HEIGHT	WITH BATTERIES 748 Kg	HEIGHT
LENGTH	LENGTH	WITH OUT BATTERIES	LENGTH
WIDTH	WIDTH		WIDTH
WHEEL BASE			WEIGHT-MIN
GROUND Clearance			WEIGHT-MAX

Vehicle shown may have optional accessories and is provide for illustrative purposes only 1 Specifications and standard equipment are subject to change without notice.







SITECRAFT 🛩

