turfman cargo



electric vehicles



High capacity 150 AMP lithium batteryFully equipped for conditional registration

• Complete with Horn, Taillights,

Blinkers, Amber Strobe

CONTACT A PRODUCT SPECIALIST 1300 363 152 | www.sitecraft.net.au

SPECIFICATION





PERFORMANCE	Cargo Standard	Cargo lifted
LOAD CAPACITY TRAY CAPACITY	500 kg 1000 x 1000	500 kg 1000 x 1000
TOWING CAPACITY	750 kg	750 kg
TURNING CIRCLE	3.5 m	3.5 m
PASSENGERS	2	2



POWER TRAIN		
MOTOR	5.0 kw AC Electric	5.0 kw AC Electric
POWER SOURCE	150 amp Specially Developed High Performance Lithium Battery To Carry Heavy Loads.	150 amp Specially Developed High Performance Lithium Battery To Carry Heavy Loads.
SYSTEM CONTROLLER	48m-350a Controller	48m-350a Controller
BATTERY CHARGER	On-Board Charger (Fully Automatic)	On-Board Charger (Fully Automatic)
MAX SPEED	Fully Adjustable - Preset 20 km/h	Fully Adjustable - Preset 20 km/h
CLIMB ABILITY	25%	25%
FRONT & REAR SUSPENSION	Front Independent Suspension with Double Wishbone and coil over Shock Absorbers all round	Front Independent Suspension with Double Wishbone and coil over Shock Absorbers all round
BRAKE SYSTEM	4 Wheel Hydraulic Disc Brakes	4 Wheel Hydraulic Disc Brakes
PARK BRAKE	Automatic Electric Engagement	Automatic Electric Engagement
WHEELS	10" Aluminum Rim with 205/65-10 Tires	12" Aluminum Rim with 23" Tires
CHASSIS		
CHASSIS / FRAME	Hot Dipped Galvanised Steel	Hot Dipped Galvanised Steel
BODY	PP Plastic with Automotive Finish	PP Plastic with Automotive Finish
ROOF	Moulded Plastic	Moulded Plastic
LIGHT	Amble Round LED System	Amble Round LED System
OPERATOR CONTROL		
STEERING	Single Stage Rack & Pinion Steering System, Automatic Rocker Compensating Function	Single Stage Rack & Pinion Steering System, Automatic Rocker Compensating Function
DIMENSION		
OVERALL DIMENSION	2785(l) × 1200 (w) × 1900 (h)	2785(I) × 1200 (w) × 1900 (h)
GROUND CLEARANCE	150 mm	170 mm





Metallic Colour Options^



^Custom colour available as per your specification